

Maintenance
of
Standard Steel Doors
and Frames



Standards As Tough As Steel.™
© 2014 Steel Door Institute

STEEL DOOR INSTITUTE
30200 DETROIT ROAD • CLEVELAND, OHIO 44145

Maintenance of Standard Steel Doors and Frames

1 Introduction

This document is intended to serve as a general outline of maintenance activities needed for standard steel doors and frames. However, it should be noted that the door and frame are virtually maintenance free. Maintenance will be, for the most part, associated with the accessories and hardware attached to the door and frame.

Maintenance of any product is important and necessary to obtain the maximum benefits of product service and longevity. Steel door and frame assemblies are not different. In fact, in some cases where the door and frame assembly is used as a "fire rated" barrier or a "leakage rated" smoke barrier, proper maintenance is crucial. Basic maintenance to ensure the proper functioning of the assembly is imperative and well worth the effort to provide for human life safety.

2 Areas to be inspected

The following items should be periodically checked. The frequency with which these checks are performed must be established at the discretion of the building owner, insurance company, labeling authority (as applicable), and maintenance service. Since doors in different areas of a building access service different traffic, the frequency of periodic inspections would occur respectively.

Hinges

Check all hinges for loose attaching screws, hinge pin wear or other notable defects. Service the hinges or remove defective parts and replace per the manufacturer's recommendations. The door should always swing freely and smoothly without obstruction from the opened to latched (when latching device is used) position.

Locksets, panic devices, fire exit hardware

Check all locksets for loose attaching screws, latch wear or other notable defects. Service the lockset or remove defective parts and replace per the manufacturer's recommendations. The door should always latch

freely and smoothly without obstruction. Self latching devices should always function freely and smoothly as the door swings into the closed position. Additional force should not be needed to achieve latching. Silencers (mutes) should be replaced when latch operation is compromised by wear.

Strike plate

The strike plate should be firmly attached to the frame or inactive leaf of a pair of doors. Check for loose screw and/or other notable defects. Service or remove and replace per the manufacturer's instructions.

Closing devices

Check all closing devices for loose attaching screws, linkage arm and pin wear, **fluid leakage** or other notable defects. Service the device or remove defective parts and replace following the manufacturer's recommendations. The primary and secondary closing speed adjustments should also be set and maintained in accordance with the manufacturer's recommendations. The device should allow the door to operate freely and smoothly throughout its entire swing range and positively latch (if so equipped) or remain in the closed position.

Flush bolts

Check all flush bolts for loose attaching screws, rod bolt adjustment and strike plate (on both door and frame if so equipped) attachment. Service the devices or remove defective parts and replace following the manufacturer's recommendations. The rod bolts should retract, extend and engage the strike or keeper hole freely and smoothly for both manual and/or automatic flush bolts.

Glass lights

The glazing material should be checked for cracks and/or missing pieces of glazing. The glazing mounting frame should be checked to assure all attaching screws (if used) are tight and the unit is securely attached to the door. Service the glass light or remove defective parts and replace by following the manufacturer's rec-

ommendations. Also be sure to use approved safety glass in appropriate applications/locations, **or fire rated glass and glazing in fire doors, windows or lights.**

Door and frame finish

A general visual inspection of the door and frame finish should be periodically conducted. Any excessive finish defects should be repaired and repainted. Adequate protection is needed to help prevent the product from rusting prematurely and shortening its service life.

Unobstructed operation

Fire rated and/or smoke control assemblies are specified and installed to meet “safety to life code requirements.” It is imperative that these assemblies receive regularly scheduled maintenance checks for all of the above items. Additionally, for the assembly to serve its purpose of stopping fire and/or smoke propagation it must function freely with the ability to positively latch in the closed position. Therefore, propping or blocking these doors in an open position is in violation of intended use and purpose as established in building

codes. These doors must not be obstructed in any fashion preventing them from functioning as intended.

Gasketing/weatherstripping

A visual and operational inspection is periodically necessary for gasketed or weatherstripped areas such as perimeter seals, threshold seals, door bottoms, etc. Inspect for signs of deterioration such as splitting, cracking or deforming of flexible components. Install replacement components as needed.

Inspect operational integrity by the following method:

Gasketing should be positioned to create proper contact along the door’s entire perimeter. The test for proper contact is usually done with common letterhead paper. The paper should be firmly held in place by inserting it between the door and gasket and then closing the door. If the paper is not firmly held in place, the seal is inadequate. The paper test should be conducted along the entire perimeter.

Related Documents:

- NFPA 80 Standard for Fire Doors and Other Opening Protectives, Chapter 5
- SDI-122 Installation and Troubleshooting Guide for Standard Steel Doors and Frames

AVAILABLE PUBLICATIONS

Specifications

- ANSI/SDI A250.6** Recommended Practice for Hardware Reinforcings on Standard Steel Doors and Frames
- ANSI/SDI A250.8** SDI 100 Specifications for Standard Steel Doors & Frames
- SDI-108** Recommended Selection & Usage Guide for Standard Steel Doors
- SDI-118** Basic Fire Door, Fire Door Frame, Transom/Sidelight Frame, and Window Frame Requirements
- SDI-128** Guidelines for Acoustical Performance of Standard Steel Doors & Frames
- SDI-129** Hinge & Strike Spacing

Test Procedures

- ANSI/SDI A250.3** Test Procedure & Acceptance Criteria for Factory Applied Finish Coatings for Steel Doors & Frames
- ANSI/SDI A250.4** Test Procedure & Acceptance Criteria for Physical Endurance for Steel Doors, Frames and Frame Anchors
- ANSI/SDI A250.10** Test Procedure & Acceptance Criteria for Prime Painted Steel Surfaces for Steel Doors & Frames
- ANSI/SDI A250.13** Testing and Rating of Severe Windstorm Resistant Components for Swinging Door Assemblies for Protection of Building Envelopes (Not applicable for FEMA 320/361 or ICC-500 Shelters)
- SDI-113** Standard Practice for Determining the Steady State Thermal Transmittance of Steel Door & Frame Assemblies
- SDI-131** Accelerated Physical Endurance Test Procedure for Steel Doors, Frames and Frame Anchors

Construction Details

- ANSI/SDI A250.11** Recommended Erection Instructions for Steel Frames
- SDI-110** Standard Steel Doors & Frames for Modular Masonry Construction
- SDI-111** Recommended Details for Standard Details Steel Doors, Frames, Accessories and Related Components
- SDI-122** Installation Troubleshooting Guide for Standard Steel Doors & Frames

Miscellaneous Documents

- SDI-112** Zinc-Coated (Galvanized/Galvannealed) Standard Steel Doors & Frames
- SDI-117** Manufacturing Tolerances for Standard Steel Doors & Frames
- SDI-124** Maintenance of Standard Steel Doors & Frames
- SDI-127** Industry Alert Series (A-L)
- SDI-130** Electrified Hinge Preparations
- SDI-134** Nomenclature for Standard Steel Doors & Steel Frames

AUDIO-VISUAL PROGRAMS ALSO AVAILABLE

MEMBERS OF THE STEEL DOOR INSTITUTE

CECO DOOR
9159 Telecom Drive
Milan, TN 38358
(731) 686-8345
www.cecodoor.com

CURRIES
P.O. Box 1648
Mason City, IA 50402-1648
(641) 423-1334
www.curries.com

DEANSTEEL MANUFACTURING CO.
931 S. Flores Street
San Antonio, TX 78204-1406
(210) 226-8271
www.deansteel.com

DOOR COMPONENTS INC.
7980 Redwood Avenue
Fontana, CA 92336-1638
(909) 770-5700
www.doorcomponents.com

HOLLOW METAL XPRESS
602 S. 65th Avenue
Phoenix, AZ 85043
623-936-7000
www.HMXpress.com

MESKER DOOR, INC.
3440 Stanwood Boulevard
Huntsville, AL 35811-9021
(256) 851-6670
www.meskerdoor.com

MPI
319 North Hills Road
Corbin, KY 40701
(606) 523-0173
www.metalproductsinc.com

PIONEER INDUSTRIES, INC.
171 South Newman Street
Hackensack, NJ 07601
(201) 933-1900
www.pioneerindustries.com

REPUBLIC DOORS & FRAMES
155 Republic Drive
McKenzie, TN 38201-0580
(731) 352-3383
www.republicdoor.com

SECURITY METAL PRODUCTS
5700 Hannum Avenue, Suite 250
Culver City, CA 90230
(310) 641-6690
www.secmct.com

STEELCRAFT
9017 Blue Ash Road
Cincinnati, OH 45242
(513) 745-6400
www.steelcraft.com



Standards As Tough As Steel.™

STEEL DOOR INSTITUTE

30200 DETROIT ROAD • CLEVELAND, OHIO 44145

440.899.0010 • FAX 440.892.1404

www.steeldoor.org